## SUBMITTAL & SPECIFICATION SHEET

## BRONLAIR

9668-D Heinrich Hertz Drive | San Diego, CA 92154 (888) 957-3448 | Romlair.com

**MODEL AF-CS** | Air Circulator, Chain Suspended **Model AF-CS** chain-suspended, high velocity fans provide an even stream of air around the work area or warehouse. They effectively distribute air to 100% of the area.

This is more desirable than pedestal fans which can only cool a limited area and often get in the way in production or warehouse operations.


The chain suspension installation is the most popular, simple, and low-cost method of installation. These high velocity fans provide an even stream of air around the work area or building, effectively distributing air to 100% of the area.

- · Chain suspended mounting
- Direct drive motor for minimal maintenance.
- Attractive deep spun14 gauge steel housing.
- Safety guards Guards are 1/2" mesh galvanized steel screen, on both the inlet and exhaust side.
- Motor mounting bracket designed to fit most standard off-theshelf motors.
- Power cord furnished on single phase units.
- Fan housing is coated with a thermally fused powdered polyurethane black finish.

DIMENSIONS & WEIGHTS

Model	A	В	С	SHIP WT
AF-CS-14	14 ½	20	16	38
AF-CS-18	19	24	16	57
AF-CS-22	22 1⁄4	29	16	61
AF-CS-30	30 ½	37	22	105

## 



QTY	MODEL	TAG	AREA OF COVERAGE (SQ FT)	DISTANCE AIR THROW (FT)	CFM	RPM	HP	VOLTS	PH	HZ	TYPE

PROJECT:	CONTRACTOR:
LOCATION:	ENGINEER:
SUBMITTED BY:	APPROVED BY:
DATE:	DATE: